

Discover how California Media Services,  
an HP Certified Partner, can meet all  
of your wide format printer needs.



(800) 986-3484



## HP SCITEX FB 950 PRINTER

### AS SPECIFIED BY OEM

<b>PRINT</b>	
Print Speed	High Quality (600 x 600 dpi): 113 ft <sup>2</sup> /hr (10.5 m <sup>2</sup> /hr) Production (600 x 600 dpi): 226 ft <sup>2</sup> /hr (21.1 m <sup>2</sup> /hr) Production (600 x 300 dpi): 455 ft <sup>2</sup> /hr (42.2 m <sup>2</sup> /hr) Billboard (600 x 300 dpi): 861 ft <sup>2</sup> /hr (80 m <sup>2</sup> /hr)
Print Resolution	1200 X 600, 600 X 600, 600 X 300 dpi
Technology	UV-curable inkjet
Ink Types	HP Scitex FB250 UV pigment inks
Ink Colors	Cyan, magenta, yellow, black, light cyan, light magenta,
Ink Drop	Variable drop size
Minimum Readable	4 points positive / 6 points negative
Text Size	
Ink Cartridge Size	3 liter <sup>1</sup>
Printheads	12 printheads (2 per color)
Cleaning Solution	HP UV Printhead Flush, 1-liter bottle
<b>MEDIA</b>	
Handling	Flatbed, sheetfed, and roll fed wth optional roll feed and take-up system Vacuum belt media drive for easy loading and accurate media advance.
Rigid Media Support	Front and rear roller tables support rigid materials from 6 x9 up to 98.4 x 80 in (15 x 23 to 250 x 203 cm). A second set of roller tables (optional) support rigid materials up to 150 in (381 cm) in length
Roll-fed Media Support	Optional roll-feed and take-up system supports up to 98.4 in (2.5 m) wide roll-fed media on 3 inch cores with an outside diameter of up to 9 inches (64 mm)
Thickness	Up to 2.5 inches (64 mm)
<b>CONNECTIVITY</b>	
Interfaces	10/100Base-T Ethernet with VideoNet protocol
<b>UV ENERGY SOURCE</b>	
	Dual shuttered UV lamps. Independent user-selectable control of shutter aperture and of three lamp power level.
<b>DIMENSIONS (W X D X H)</b>	
Printer	160 x 48 x 61 in (406 x 122 x 155 cm)
Printer With Tables	160 x 128 x 61 in (406 x 325 x 155 cm)
Shipping	171 x 63 x 72 in (434 x 160 x 182 cm)
<b>WEIGHT</b>	
	Printer: 1507 lb Printer with tables: 1657 lb Shipping: 2473 lb
<b>WHAT'S IN THE BOX</b>	
	HP Scitex FB950 Printer, HP Scitex FB250 ink (6 x 1 L) UV printhead flush (2 L), input and output roller tables, 25 ft (7.6 ) VideoNet interface cable, documentation
<b>Operating conditions</b>	
Temperature	68 to 85°F (20 to 30° C)
Humidity	20 to 80% RH (non-condensing)
<b>POWER</b>	
	200 TO 240 vac, 3-PHASE, 50/60 Hz, 12 A max
<b>WARRANTY</b>	
	One-year limited hardware warranty

### Ordering Information

<b>ACCESSORIES</b>	
CH231A	HP UV Replacement Bulb
CH151A	HP Scitex 12-pack UV Lamp Air Filters
CH240A	HP Scitex Second Set Roller Table
CM763A	HP Scitex FB900 Roll to Roll Kit
CH242A	HP Scitex FB900 Phase Converter Plug Kit
CM761A	HP Scitex FB950 Exhaust Kit
<b>RIPs</b>	
CH224A	HP with Color Profiling RIP Software
CH226A	HP RIP Software Upgrade
<b>INK CARTRIDGES</b>	
CH216A	HP Scitex FB250 Cyan Ink
CH217A	HP Scitex FB250 Magenta Ink
CH218A	HP Scitex FB250 Yellow Ink
CH219A	HP Scitex FB250 Black Ink
CH220A	HP Scitex FB250 Light Cyan Ink
CH221A	HP Scitex FB250 Light Magenta Ink
CH122A	HP UV Printhead Flush

<sup>1</sup> 1 liter cartridges included with printer as start up kit, replacement inks sold in 3 liter cartridges only

For more information, please visit: [www.cmscalmedia.com](http://www.cmscalmedia.com)

© Copyright 2008 Hewlett-Packard Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.